

MP CAN

Adapted to vehicles with CAN Bus communication



Characteristics

- Multiband Radio with Full-Duplex communication.
- External LEDs for troubleshooting.
- Highly field-customizable.
- Removable EEPROM SIM module.
- Frequencies management against interferences.
- STOP: PLd, Category 3 according to EN ISO 13849-1:2008.
- Easy and fast maintenance.
- Multi-feedback capability.
- 4 digital outputs/inputs.
- CANopen, Profibus-DP, J1939, IQAN

Specifications

Receiver	MPCAN
Stop Function	Cat. 3 - PLd.
Ingress protection	IP65/NEMA4.
Frequency Band	Multiband (400 - 930 MHz).
AC Power Supply	na.
DC Power Supply	9 -35 Vdc.
Antenna	External / Internal (default)
Removable EEPROM	Internal.
Signalling	External.
ON/OFF outputs (Max.)	4.
Analogue Outputs (Max.)	na.
CANOpen, Profibus-DP, SAE J1939	YES.
ON/OFF inputs (Max.)	4.
Analogue Inputs (Max.)	na
Maximum output Current	2A.
Working Temperature Range	-20C +70C (-4F +158F).
Weight (gr)	300.
Dimensions (LxWxH mm)	117x133x36.
Cable connection	YES.
Associated Transmitters	T70/1, T70/2, T70/3, T70/4, IK3, T70/1HALL, T70/2HALL, T70/1 ATEX, T70/2ATEX.



HEADQUARTERS

IKUSI · Pº Miramón, 170 · 20014 Donostia-San Sebastián · SPAIN
 Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · tlc@ikusi.com · www.ikusiremotecontrol.com

IKUSI WORLDWIDE

AUSTRALIA · CHILE · COLOMBIA · FRANCE · GERMANY · MEXICO · SPAIN · UNITED ARAB EMIRATES · USA



Leading Brands of Spain Forum